PURDUE AGRICULTURE

Introduction

The measurement and characterization of soil physical properties at the field scale is increasingly important in agriculture and natural resource management. Changes in topography, parent material, management practices, erosion, etc., can influence the variability of the soil's physical properties. The Geonics EM38 is a noninvasive geophysical sensor that is used to measure the soils apparent electrical conductivity (Ec_a in milliSiemens/meter) through electromagnetic induction – primarily influenced by clay content, soil moisture content, and salinity. Soil moisture is a significant contributor to Ec_a, allowing the EM38 to be used to measure both the spatial and temporal variation in Available Water Content (AWC) across a landscape. This study combined detailed lab analysis of soil physical properties at 14 discrete locations, within the same field, with EM38 surveys to examine the ability of EM38 to quantify and map soils based on their physical properties and surface soil moisture (0-15cm) in the root zone.

Objectives

- Determine the ability of an EM38 sensor to measure the spatial variability of soil physical properties at the field scale in coarse-textured/gravelly Piedmont soils of North Carolina and map characteristics using a Geographic Information System (GIS)
- Calibrate and test the sensors ability to measure temporal variability of soil moisture in the root zone

Significance

The ability of an EM38 sensor to perform real-time, on-the go sensing of key soil properties, such as soil moisture, means high resolution maps can be developed that will significantly aid in our understanding and management of soils. These maps can be used to direct soil sampling, placement of soil moisture sensors, and the delineation of management zones/soil restoration areas.

Materials and Methods

Study site description:

- A 1.65 hectare field at the NCSU Lake Wheeler Road Field Laboratory (LWRFL) in the Piedmont region of North Carolina (Fig. 2) was selected as the study site.
- The site was selected based on an initial EM38 survey, variable topography, input from • LWRFL superintendent, cropping rotation, feasibility of in-season research, and proximity to NCSU campus.



Materials:

- Geonics EM38 geophysical sensor (Fig. 1) and • 1.5 m tall PVC calibration stand
- Trimble Nomad 9600 DGPS (Differential GPS) unit with Farmworks Mobile 6.1 Software
- Slide hammer soil core sampler with sampling head and core sleeves
- Soil Push Probe



Fig. 1: EM38 sensor in horizontal dipole position at field site



Sampling Points Field Boundary

Experimental Methods

Fig. 2: Aerial image acquired at early season corn growth (V7) 6/26/2015

Soil Physical Properties:

- Soil cores were collected along 3 transects (Fig. 2)
- bulk density, volumetric water content, particle size, and water retention

EM38 Measurements:

- Discrete EM38 readings collected at each of the 14 locations
- Six readings were taken within a 2m² area around each sample point
- were collected to calibrate EC_a to soil moisture

EM38 Survey:

spacing on two separate dates (Fig. 5)

Results

Soil Physical Properties

- Particle size analysis indicates small range of textural variation (Fig. 3)
- Gravel fraction within cores varied from 5% to 50% of soil core mass
- Available Water Content varied by 8% between core samples (Fig. 7)

EM38 and Soil Physical Properties

- 52% of EC_a value explained by the clay fraction of the soil matrix (Fig. 4)
- No significant relationship was observed between EC_a and bulk density



Fig. 5: Point data of EM38 survey taken 6/26/2015, excluding outliers



of soil profile at sample points

appreciate support of C. Niewoehner for guidance in lab analyses; J. Taylor and I. Holzer for field data collection; and NextGen Air Transportation (NGAT) for aerial imagery.